

AIR TOOLS



BELT SANDERS

- Ergonomic design
- Low maintenance motor
- Easy belt changes
- Unequaled power to weight ratio



Model No.	Mfg. No.	Free Speed RPM	Belt Size L x l		Power		Weight		Air Consumption At Free Speed		Air Inlet Thread"	Hose I.D."	Price /Each
			in.	mm	HP	W	lbs.	kg	CFM	L/s			
TCW005	CP9779	22000	13 x 3/8	330 x 10	0.4	300	2.09	0.95	14	6	1/4	3/8	
TCW006	CP9780	20000	20.4 x 3/4	520 x 20	0.4	300	2.09	0.95	15	7	1/4	3/8	

UTILITY HAMMERS

For light to medium duty chipping, trimming, riveting, cutting, piercing & peening jobs

- Aluminum body
- 2 5/8" stroke (TG087), 3 1/2" stroke (TG088)
- Piston air-cushioned on return stroke
- 1/4" (NPTF) air inlet
- 3/8" minimum air hose size



Model No.	Mfg. No.	Capacity Cold Rivets in. (mm)		Bore and Stroke in. (mm)	Blows per Minute	Rivet Set and Chisel Shank CFM	dBa	Vibration m/s ²	Overall Length in. (mm)	Net Weight lbs. (kg)	Price /Each
		Dural	Steel								
TG087	CP7111	1/4 (6.4)	3/16 (4.8)	3/4 x 2 5/8 (19 x 67)	3000	0.401 (10.19 mm)	25	100	8.9	6 3/4 (171)	3 1/2 (1.6)
TG088	CP7150	5/16 (7.9)	1/4 (6.4)	3/4 x 3 1/2 (19 x 89)	2300	0.401 (10.19 mm)	25	100	9.4	8 7/8 (225)	4.2 (1.9)

Noise levels are at 1.0 m per Pneurop Standard 8N-1. Vibration levels are per ISO 8662-1.

INDUSTRIAL CHIPPERS/SCALERS

- For industrial use
- Powerful
- Durable



Model No.	Mfg. No.	Bore		Stroke		Blows Per Minute	Weight		Air Consumption At Free Speed		Air Inlet Thread"	Hose I.D."	Price /Each
		in.	mm	in.	mm		Shank"	lbs.	kg	CFM			
TCW253	CP9356NS	0.71	18.0	1.18	30.0	ISO 1/2 square	3.3	1.5	3.0	1.4	1/4	5/16	
TCW235	CP9356WF	0.93	23.5	1.40	35.6	ISO 1/2 square	4.4	2.0	5.5	2.6	1/4	3/8	
TCW108	CP0952	1.30	33.0	1.94	49.2	ISO 1/2 square	8.8	4.0	8.5	4.0	1/4	3/8	

Chisel not included